



DUALCOM PRO - REQUIRED ACCESSORIES FOR REGRADING

REGRADE OPTIONS

DualCom Pro - Required Accessories for Regrading

Regrade Options

| | | To: Radio Only | To: LAN Only | To: LAN/Radio | To: Radio/Radio |
|----------------|----------------------------------|--|--|--|--|
| DigiAir Pro | From: Radio Only | N/A | Ethernet Cable - CS.1.301 LAN Adaptor - CS.1.30* | Ethernet Cable - CS.1.301 LAN Adaptor - CS.1.302 | DualCom Pro 4G Radio Module - CS.40.105 |
| | From: LAN Only | DigiAir Pro 3 - Radio Only CS.51.HWL** | N/A | GradeShift Pro 2 - LAN/Radio CS.53.HW ** | GradeShift Pro 2 - Radio/Radio CS.55.HW ** |
| GradeShift Pro | From: LAN/Radio | No Accessory / Hardware Needed * | No Accessory / Hardware Needed* | N/A | DualCom Pro 4G Radio Module - CS.40.105 |
| | From: GradeShift Pro Radio/Radio | No Accessory / Hardware Needed * | Ethernet Cable - CS.1.301 LAN Adaptor - CS.1.302* | Ethernet Cable - CS.1.301 LAN Adaptor - CS.1.302* | N/A |

| | | | | | |
|------------------|-------------------|--|----------------------------------|--|--|
| DigiAir Pro 2 | From: Radio Only | N/A | Ethernet Cable - CS.1.301* | Ethernet Cable - CS.1.301 | DualCom Pro 2 4G Radio Module - CS.40.105 |
| | From: LAN Only | DigiAir Pro 3 - Radio Only CS.51.HWL** | N/A | GradeShift Pro 2 - LAN/Radio CS.53.HW ** | GradeShift Pro 2 - Radio/Radio CS.55.HW ** |
| GradeShift Pro 2 | From: LAN/Radio | No Accessory / Hardware Needed * | No Accessory / Hardware Needed * | N/A | DualCom Pro 2 4G Radio Module - CS.40.105 |
| | From: Radio/Radio | No Accessory / Hardware Needed * | Ethernet Cable - CS.1.301 * | Ethernet Cable - CS.1.301 * | N/A |

| | | | | | |
|---------------|---------------------|--|--|---|---|
| DigiAir Pro 3 | From: Radio Only | N/A | DigiAir Pro 3 - LAN Only CS.51.HWR** | GradeShift Pro 2 - LAN/Radio CS.53.HW ** | GradeShift Pro 2 - Radio/Radio CS.55.HW ** |
| | From: LAN Only | DigiAir Pro 3 - Radio Only CS.51.HWL** | N/A | GradeShift Pro 2 - LAN/Radio CS.53.HW ** | GradeShift Pro 2 - Radio/Radio CS.55.HW ** |

* the device needs to be installed for at least 12 months before being eligible for a regrade.

** a new DualCom Pro device is also required to complete the regrade.